

Code: **P101014100**Product: **AS-221000-101**

Std Description: SMOOTHWALL RECT. TRAY

Customer Description:

General Features

Body Style: SMOOTH WALL
Body Shape: RECTANGULAR
Flange Style: FLAT
Rim Style: REVERSE FULL CURL
Base Feature: STANDARD
Material: ALUMINIUM
Outside Lacquer:
Inside Lacquer:
Lidding Suitability: FILM SEAL
Scope of temperature: -40°C to 300°C
General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with uncoated aluminium should be avoided. A packaging test must always be carried out by the food manufacturer
Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983 following instructions that can be found at www.alufoil.org/alufoil-and-microwave-ovens.html

General Dimensions

Top Out (mm) ±0.5:	220.0 x 150.0
Top In (mm) ±0.5:	202.0 x 132.0
Base (mm) ±0.5:	186.0 x 116.0
Vertical Depth (mm) ±0.5:	45.0
Cubic Capacity (cm³):	1,000
Gauge (mm) ±8%:	0.100
Temper:	H22
Net Container Weight (gms) ±8%:	15.3

Pack Features

Pack Quantity: 660
Poly Sleaving: Yes - Blue Tint
Poly Liner: No
Carton Size (L x W x H): 500 x 405 x 320
Pack Volume (M³): 0.060
Net Pack Weight (kg): 10.1
Gross Pack Weight (kg): 11.0

Pallet Features

Pallet Type: UK-1200-1000-140-STD
Pallet Edge Protection: No
Cartons per Layer: 6
Layers per Pallet: 5
Cartons per Pallet: 30
Containers per Pallet: 19,800
Pallet Dimensions (L x W x H): 1200 x 1000 x 1740
Gross Pallet Volume (M³): 1.800
Gross Pallet Weight (kg): 345

Product manufactured in the United Kingdom
 All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Date of Issue: April 2014

Version No' 3.0

Authorised:



Chief Executive Officer



This specification is the property of i2r Packaging Solutions Limited and should not be copied or disclosed to anyone without the written consent of the Company