Product Specification Data Sheet



Code: P10102607P

Product: AS-223320-101

Std Description: SMOOTHWALL RECT. TRAY

Customer Description:

General Features

Body Style: SMOOTH WALL Body Shape: RECTANGULAR

Flange Style: FLAT

Rim Style: REVERSE FULL CURL

Base Feature: STANDARD
Material: ALUMINIUM

Outside Lacquer: Inside Lacquer:

Lidding Suitability: FILM SEAL Scope of temperature: -40°C to 300°C

General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with

uncoated aluminium should be avoided. A packaging test must always

be carried out by the food manufacturer

Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983

following intructions that can be found at www.alufoil.org/alufoil-and-

microwave-ovens.html

General Dimensions

 Top Out (mm) ±0.5:
 312.0 x 244.0

 Top In (mm) ±0.5:
 288.0 x 220.0

 Base (mm) ±0.5:
 262.0 x 194.0

 Vertical Depth (mm) ±0.5:
 60.0

 Cubic Capacity (cm³):
 3,320

 Gauge (mm) ±8%:
 0.150

 Temper:
 H22

Net Container Weight (gms) ±8%: 48.8

Pack Features

Pack Quantity: 140

Poly Sleeving: Yes - Blue Tint

Poly Liner: No

Carton Size (L x W x H): 405 x 305 x 320

Pack Volume (M³): 0.036 Net Pack Weight (Kg): 6.8 Gross Pack Weight (Kg): 7.7

Pallet Features

Pallet Type: UK-1200-1000-140-STD

Pallet Edge Protection: No Cartons per Layer 10 Layers per Pallet 5 Cartons per Pallet: 50 Containers per Pallet: 7,000

Pallet Dimensions (L x W x H): 1200 x 1000 x 1740

Gross Pallet Volume (M³): 1.806 Gross Pallet Weight (kg): 398

Product manufactured in the United Kingdom

All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Date of Issue: April 2014

Authorised:

Chief Executive Officer

Version No' 3.0

