Product Specification Data Sheet



Code: P10102200R

Product: AS-221534-101

Std Description: SMOOTHWALL RECT. TRAY

Customer Description:

General Features

Body Style: SMOOTH WALL Body Shape: RECTANGULAR

Flange Style: FLAT

Rim Style: REVERSE FULL CURL

Base Feature: STANDARD
Material: ALUMINIUM

Outside Lacquer: Inside Lacquer:

Lidding Suitability: FILM SEAL Scope of temperature: -40°C to 300°C

General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with

uncoated aluminium should be avoided. A packaging test must always

be carried out by the food manufacturer

Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983

following intructions that can be found at www.alufoil.org/alufoil-and-

microwave-ovens.html

General Dimensions

 Top Out (mm) ±0.5:
 220.0 x 150.0

 Top In (mm) ±0.5:
 202.0 x 132.0

 Base (mm) ±0.5:
 180.0 x 110.0

 Vertical Depth (mm) ±0.5:
 70.0

 Cubic Capacity (cm³):
 1,534

 Gauge (mm) ±8%:
 0.125

 Temper:
 H22

Net Container Weight (gms) ±8%: 22.8

Pack Features

Pack Quantity: 600

Poly Sleeving: Yes - Blue Tint

Poly Liner: No

Carton Size (L x W x H): 500 x 405 x 320

Pack Volume (M³): 0.060 Net Pack Weight (Kg): 13.7 Gross Pack Weight (Kg): 14.6

Pallet Features

Pallet Type: UK-1200-1000-140-STD

Pallet Edge Protection: No
Cartons per Layer 6
Layers per Pallet 5
Cartons per Pallet: 30
Containers per Pallet: 18,000

Pallet Dimensions (L x W x H): 1200 x 1000 x 1740

Gross Pallet Volume (M³): 1.800 Gross Pallet Weight (kg): 453

Product manufactured in the United Kingdom

All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Date of Issue: April 2014

Authorised:

Chief Executive Officer

Version No' 3.0

