Product Specification Data Sheet



Code: P10100800P

Product: AS-220763-101

Std Description: SMOOTHWALL RECT. TRAY

Customer Description:

General Features

Body Style: SMOOTH WALL Body Shape: RECTANGULAR

Flange Style: FLAT

Rim Style: REVERSE FULL CURL

Base Feature: STANDARD
Material: ALUMINIUM

Outside Lacquer: Inside Lacquer:

Lidding Suitability: FILM SEAL Scope of temperature: -40°C to 300°C

General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with

uncoated aluminium should be avoided. A packaging test must always

be carried out by the food manufacturer

Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983

following intructions that can be found at www.alufoil.org/alufoil-and-

microwave-ovens.html

General Dimensions

Top Out (mm) ±0.5: 178.0 x 136.0 Top In (mm) ±0.5: 164.0 x 122.0 Base (mm) ±0.5: 148.0 x 106.0

 Vertical Depth (mm) ±0.5:
 45.0

 Cubic Capacity (cm³):
 763

 Gauge (mm) ±8%:
 0.100

 Temper:
 H22

Net Container Weight (gms) ±8%: 11.8

Pack Features

Pack Quantity: 500

Poly Sleeving: Yes - Blue Tint

Poly Liner: No

Carton Size (L x W x H): 405 x 305 x 320

Pack Volume (M³): 0.036 Net Pack Weight (Kg): 5.9 Gross Pack Weight (Kg): 6.7

Pallet Features

Pallet Type: UK-1200-1000-140-STD

Pallet Edge Protection: No
Cartons per Layer 10
Layers per Pallet 5
Cartons per Pallet: 50
Containers per Pallet: 25,000

Pallet Dimensions (L x W x H): 1200 x 1000 x 1740

Gross Pallet Volume (M³): 1.806 Gross Pallet Weight (kg): 352

Product manufactured in the United Kingdom

All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Version No' 2.0

Date of Issue: April 2014

Authorised:

Chief Executive Officer

packaging BRC

This specification is the property of i2r Packaging Solutions Limited and should not be copied or disclosed to anyone without the written consent of the Company