

Code: P10102501P

Product: AS-222371-101

Std Description: SMOOTHWALL RECT. TRAY

Customer Description: AS-222371-101

General Features

Body Style: SMOOTH WALL
Body Shape: RECTANGULAR
Flange Style: FLAT
Rim Style: REVERSE FULL CURL
Base Feature: STANDARD
Material: ALUMINIUM
Outside Lacquer:
Inside Lacquer:
Lidding Suitability: FILM SEAL
Scope of temperature: -40°C to 300°C
General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with uncoated aluminium should be avoided. A packaging test must always be carried out by the food manufacturer
Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983 following instructions that can be found at www.alufoil.org/alufoil-and-microwave-ovens.html

General Dimensions

Top Out (mm) ±0.5: 265.0 x 165.0
Top In (mm) ±0.5: 247.0 x 147.0
Base (mm) ±0.5: 230.7 x 130.7
Vertical Depth (mm) ±0.5: 75.0
Cubic Capacity (cm³): 2,371
Gauge (mm) ±8%: 0.125
Temper: H22
Net Container Weight (gms) ±8%: 29.9

Pack Features

Pack Quantity: 200
Poly Sleaving: Yes - Blue Tint
Poly Liner: No
Carton Size (L x W x H): 405 x 305 x 320
Pack Volume (M³): 0.036
Net Pack Weight (kg): 6.0
Gross Pack Weight (kg): 6.8

Pallet Features

Pallet Type: UK-1200-1000-140-STD
Pallet Edge Protection: No
Cartons per Layer: 10
Layers per Pallet: 5
Cartons per Pallet: 50
Containers per Pallet: 10,000
Pallet Dimensions (L x W x H): 1200 x 1000 x 1740
Gross Pallet Volume (M³): 1.806
Gross Pallet Weight (kg): 356

Product manufactured in the United Kingdom
 All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Date of Issue: April 2014

Version No' 3.0

Authorised:



Chief Executive Officer



This specification is the property of i2r Packaging Solutions Limited and should not be copied or disclosed to anyone without the written consent of the Company