

Code: P10101000P**Product:** AS-220859-101**Std Description:** SMOOTHWALL RECT. TRAY**Customer Description:** AS-220859-101**General Features**

Body Style: SMOOTH WALL
Body Shape: RECTANGULAR
Flange Style: FLAT
Rim Style: REVERSE FULL CURL
Base Feature: STANDARD
Material: ALUMINIUM
Outside Lacquer:
Inside Lacquer:
Lidding Suitability: FILM SEAL
Scope of temperature: -40°C to 300°C
General Usage: The storage of strongly acidic or strongly salted foodstuffs in contact with uncoated aluminium should be avoided. A packaging test must always be carried out by the food manufacturer
Microwave Usage: Aluminium is safe to use in microwave ovens constructed after 1983 following instructions that can be found at www.alufoil.org/alufoil-and-microwave-ovens.html

General Dimensions

Top Out (mm) ±0.5: 197.0 x 155.0
Top In (mm) ±0.5: 179.0 x 137.0
Base (mm) ±0.5: 164.0 x 122.0
Vertical Depth (mm) ±0.5: 40.0
Cubic Capacity (cm³): 859
Gauge (mm) ±8%: 0.105
Temper: H22
Net Container Weight (gms) ±8%: 14.5

Pack Features

Pack Quantity: 480
Poly Sleeving: Yes - Blue Tint
Poly Liner: No
Carton Size (L x W x H): 405 x 305 x 320
Pack Volume (m³): 0.036
Net Pack Weight (kg): 6.9
Gross Pack Weight (kg): 7.8

Pallet Features

Pallet Type: UK-1200-1000-140-STD
Pallet Edge Protection: No
Cartons per Layer: 10
Layers per Pallet: 5
Cartons per Pallet: 50
Containers per Pallet: 24,000
Pallet Dimensions (L x W x H): 1200 x 1000 x 1740
Gross Pallet Volume (m³): 1.806
Gross Pallet Weight (kg): 403

Product manufactured in the United Kingdom
 All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

Date of Issue: April 2014

Version No' 1.0

Authorised:


 Chief Executive Officer


This specification is the property of i2r Packaging Solutions Limited and should not be copied or disclosed to anyone without the written consent of the Company